

## RL78/G14 シリーズ用パラメーターファイル Ver1.13

Parameter File for RL78/G14 Series

RL78\_G14\_30pin\_Ver1\_01.prs

RL78\_G14\_32pin\_Ver1\_01.prs

RL78\_G14\_44pin\_Ver1\_02.prs

RL78\_G14\_48pin\_Ver1\_00.prs

RL78\_G14\_52pin\_Ver1\_01.prs

**RL78\_G14\_64pin\_Ver1\_02.prs**

RL78\_G14\_80pin\_Ver1\_03.prs

RL78\_G14\_100pin\_Ver1\_00.prs

補足資料

Supplement Documentation

## StickWriter (Single Type)

対応デバイス 一覧表

The correspondence device list

RL78_G14_30pin_Ver1_01.prs	R5F104AA (16K+4K) R5F104AD (32K+4K)
RL78_G14_32pin_Ver1_01.prs	R5F104BC (32K+4K) R5F104BD (48K+4K) R5F104BF (96K+8K)
RL78_G14_44pin_Ver1_02.prs	R5F104FC (32K+4K) R5F104FE (64K+4K)
RL78_G14_48pin_Ver1_00.prs	R5F104GG (128K+8K) R5F104GL (512K+8K)
RL78_G14_52pin_Ver1_01.prs	R5F104JF (96K+8K) R5F104JG (128K+8K)
<b>RL78_G14_64pin_Ver1_02.prs</b>	R5F104LE (64K+4K) <b>R5F104LG (128K+8K)</b> R5F104LJ (256K+8K)
RL78_G14_80pin_Ver1_03.prs	R5F104MG (128K+8K) R5F104MH (192K+8K) R5F104MJ (256K+8K) R5F104MK (384K+8K) R5F104ML (512K+8K)
RL78_G14_100pin_Ver1_00.prs	R5F104PJ (256K+8K)

ソフトウェア 対応表  
Correspondence version

	Version
StickWriter Ver.2 GUI	Ver2.27 or later
StickWriter Ver.2 F/W	Ver3.29 or later

注意事項)

Notes)

1. 通信方式は単線 UART(TOOL0)のみに対応しています。

The communication mode is supporting only single-line UART (TOOL0).